

SWIT®

7-in AC/DC PORTABLE MONITOR (3G-SDI, HDMI, COMPOSITE)

S-1071H



Introduction:

The S-1071H is a 7-inch 3G/HD/SD-SDI/HDMI on-camera monitor with 1024 x 600 resolution, H/V: 160/160 viewing angle and 900:1 contrast ratio. It has front & rear dual TALLY lights, Canon DSLR scale zoom-in, video flip, customer editable video title, and safety mark display.

The monitor accepts 1 3G/HD/SD-SDI, 1 HDMI, 1 Composite video, 1 stereo audio input, and has 1 3G/HD/SD-SDI, 1 HDMI and 1 Composite video loop through output.

It's powered via a 4-pin XLR 6.5-17V DC connector or V-mount / Gold-mount / Snap-on DV battery mounts.

Features:


- ◆ 1024×RGB×600
- ◆ 16:9 / 4:3 adjustable
- ◆ 3G/HD/SD-SDI, HDMI, Composite video, Stereo audio inputs
- ◆ Dual 3-color TALLY light
- ◆ Underscan / Overscan switch
- ◆ Canon DSLR scale zoom-in
- ◆ Video flip
- ◆ Customer editable video TITLE
- ◆ SDI embedded audio output
- ◆ V-mount / Gold mount option
- ◆ Snap-on DV mounts option

Simple Package includes:



Cold shoe / Screw Head Sun Hood Battery mount LCD Protector 4-pin XLR AC-DC adapter

Luxury Package has additional:



S-7107 HDMI cable with mini HDMI adaptor S-7101 D-tap to 4-pin XLR cable Pan-tilt arm trestle (screw mount) Carrying case

Specifications:

LCD Performance

Size	7.0 inches
Resolution	1024×RGB×600
Aspect ratio	16:9/4:3
Color system	NTSC/PAL
Brightness	400cd/m2
Contrast	900:1
Color	16.77 million colors
Viewing angle	H/V:160/160

Input and Output

Input	1 BNC	1 3G/HD/SD-SDI in
	1 BNC	1 Composite in
	1 HDMI	1 HDMI in
	2 RCA	Stereo audio (L, R) in
Output	1 BNC	1 3G/HD/SD-SDI loop through out
	1 BNC	1 Composite loop through out
	1 HDMI	1 HDMI loop through out

Video Format

SDI	SMPTE-425M	1080P (60 / 59.94 / 50)
		1080i (60 / 59.94 / 50)
	SMPTE-274M	1080p (30 / 29.97 / 25 / 24 / 23.98)
		720p (60 / 59.94 / 50)
	SMPTE-296M	480i (59.94)
ITU-R BT.656	576i (50)	
HDMI	480i / 576i / 480P / 576P	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
Composite	PAL/NTSC	

General

Working voltage	DC/Battery 6.5V-17V
Power consumption	≤ 8W
Working temperature	0 C ~ +40 C
Working humidity	10% ~ 90%
Storage temperature	-15 C ~ +60 C
Storage humidity	10% ~ 90%
Dimensions	192×139×47mm
Net weight	550g

SWIT Electronics Co., Ltd.

Website: www.swit.cc
Email: contact@swit.cc
Tel: +86 25 85805753
Fax: +86 25 85805296

Distributed by:

GLOBALMEDIAPRO, s.r.o.
Tel: +420 604832235

E-mail: sales@globalmediapro.cz