

SWIT®



S-1093F 9" Full HD Broadcast LCD Monitor

■ Features

- ◆ 9" IPS LCD, 1920 × 1200, H/V 170° viewing
- ◆ Build-in LCD protective glass
- ◆ 2K/3G/HD/SD-SDI, HDMI, CVBS monitoring
- ◆ 16-ch Embedded audio meters with alert
- ◆ Select any 2 audio channels to output
- ◆ Waveform Y/Cb/Cr/R/G/B and single line
- ◆ Vector scope, histogram R/G/B/Y
- ◆ AFD, H/V delay, R/G/B/Mono, False color
- ◆ TSL UMD and text TALLY display
- ◆ Zebra stripes, Peaking focus assist
- ◆ SDI timecode display
- ◆ Marker 4:3, 13:9, 14:9, 15:9, 1.85:1, 2.35:1
- ◆ Front / Rear TALLY light and GPI control
- ◆ V-mount, Gold mount or snap-on DV mount
- ◆ USB firmware upgrade

■ Simple package includes



Sun hood



Articulating arm
1/4" or cold shoe



4-pin XLR
power adaptor



V-mount / Gold mount /
DV mount optional

■ Luxury package has additional



Carrying case



D-tap to 4-pin XLR
DC cable



U shape desktop stand

■ Specification

| LCD Performance | | |
|------------------------|--|--|
| Size | 9 inches | |
| Display area | 191.5 × 119.7 mm | |
| Resolution | 1920 × 1200 | |
| Color | 8 bit | |
| Aspect ratio | 16:9 (4:3 adjustable) | |
| Brightness | 450 cd/m ² | |
| Contrast | 1000:1 | |
| Viewing Angle | H/V:170° / 170° | |
| Input/output | | |
| Input | BNC × 2 | 2K/3G/HD/SD-SDI input × 2 |
| | BNC × 1 | CVBS input |
| | HDMI-A × 1 | HDMI input |
| | GPI × 1 | UMD, GPI × 1 |
| | 3.5mm × 1 | analog audio input |
| Output | BNC × 2 | 2K/3G/HD/SD-SDI loop output × 2 |
| | BNC × 1 | CVBS loop output |
| | HDMI-A × 1 | HDMI loop output |
| | 3.5mm × 1 | SDI/HDMI/analog audio output |
| Video Format | | |
| SDI | SMPTE ST 2048-1: 2011 | 2048 × 1080p (60 / 59.94 / 50 / 24 / 24sF / 23.98 / 23.98sF) |
| | SMPTE-425M-A/B | 1080p (60 / 59.94 / 50) |
| | SMPTE-274M | 1080i (60 / 59.94 / 50) |
| | | 1080p (30 / 29.97 / 25 / 24 / 23.98) |
| | SMPTE-RP211 | 1080psf (30 / 29.97 / 25 / 24 / 23.98) |
| | SMPTE-296M | 720p (60 / 59.94 / 50) |
| HDMI | SMPTE-125M | 480i (59.94) |
| | ITU-R BT.656 | 576i (50) |
| | | 480i / 576i / 480p / 576p |
| | | 1080i (60 / 59.94 / 50) |
| | 720p (60 / 59.94 / 50) | |
| | 1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98) | |
| | 1080psf (30 / 29.97 / 25 / 24 / 23.98) | |
| CVBS | NTSC / PAL | |
| General | | |
| Input voltage | DC 6.5V-24V | |
| Power consumption | 18W | |
| Working temperature | 0°C ~ +40°C | |
| Working humidity | 10% ~ 90% | |
| Storage temperature | - 15°C ~ + 60°C | |
| Storage humidity | 10% ~ 90% | |
| Dimensions | 241 × 178 × 50mm | |
| Net weight (main body) | 960g | |

SWIT Electronics Co., Ltd.

Website: www.swit.cc Tel: +86 25 85805753
Email: contact@swit.cc Fax: +86 25 85805296

Distributed by:

GLOBALMEDIAPRO, s.r.o.
www.globalmediapro.cz
Tel: +420 604832235