Wireless HD Transmission System

S-4901S, S-4902S

Introduction:

The SWIT wireless HD transmission system adopts professional WHDI (MIMO/OFDM) technology, supports uncompressed 3G/HD/SD-SDI transmission in 50-100 meters scale, with less than 1ms latency, auto selecting 5.1GHz-5.9GHz frequency, license free.

Wireless Method

Professional WHDI (MIMO/OFDM) wireless module

Uncompressed 3Gb/s SDI transmission

Up to 1080p 50/60 uncompressed SDI wireless transmission

50-100 meters transmission distance

The effective transmission distance is 50 meters, and in open outdoor space, the wireless distance could be extended to about 100 meters.

Less than 1ms latency

There's no discernible video delay and you can use it as real time on-location monitoring.

License free operation frequency

The wireless frequency is 5.1-5.9GHz, license free operated.

Input/Output

S-4901S transmitter supports 1 SDI input and 1 SDI loop output S-4902S receiver supports 2 SDI output

SDI embedded audio transmission

2-ch SDI embedded audio supported

Multicast supported

You can use 1 transmitter to broadcast to multi receivers wirelessly.

Encryption

Support AES 128-bit encryption to protect the transmission

V-mount application

Both of the transmitter and receiver are V-mount adaptor, for V-mount batteries and cameras.









Specifications:

Model			S-4901S	S-4902S
Input			3G/HD/SD-SDI input ×1	Wireless receiving
Output			Wireless transmitting, 3G/HD/SD-SDI loop out ×1	3G/HD/SD-SDI output ×2
Format	SDI	SMPTE-425M	1080p(60/59.94/50)	
		SMPTE-274M	1080p(30/29.97/25/24/23.98)/1080i(60/59.94/50)	
		SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)	
		SMPTE-296M	720p(60/59.94/50)	
		SMPTE-125M	480i(59.94)	
		ITU-R BT.656	576i(50)	
	Wireless Frequency		5.1 – 5.9GHz License-free	
General	Input voltage		DC / battery 6.5-17V	
	Power consumption		≤10W	
	Working environment		Temperature: 0°C -+40°C, Humidity:10%-95%	
	Dimension		196×145×56mm (w/o antenna)	
	Net weight		527g	555g

SWIT Electronics Co., Ltd.

Website: www.swit.cc Email: contact@swit.cc Tel: +86 25 85805753 Fax: +86 25 85805296 **Distributed by:**

GLOBALMEDIAPRO, s.r.o.

Tel: +420 775122666

E-mail: sales@globalmediapro.cz Website: http://www.globalmediapro.cz